



CAB4/1C/AB 4 Core Alarm Cable  
Carton ADI Benelux

100mtr

**Construction**

Group	Signal Cores	Power Cores
<b>Conductor</b>		
Material	Tinned annealed stranded Cu	n/a
Nominal Diameter	Ø 0.546mm = 7xØ 0.182mm	n/a
Area	0.182mm <sup>2</sup>	n/a
<b>Insulation</b>		
Material	Type 2, Type TI 1PVC	n/a
Nominal Diameter	Ø 1.0mm	n/a
Min wall	0.2mm	n/a
Colours	<i>see colour table</i>	n/a
<b>Mylar Layer</b>		
Coverage	n/a	
<b>Drain Wire</b>		
Material	n/a	
Nominal Diameter	n/a	
Area	n/a	
<b>Screen</b>		
Material	n/a	
Coverage	n/a	
Rip cord	Polyester 1100 Desitex 40 Nm breaking strain.	
<b>Sheath</b>		
Material	Tubed PVC Type 6, Type TM 1	
Colour	White	
Nominal Diameter	Ø 3.4mm	
Min wall	Ø 0.4mm	
<b>Sheath Marking</b>		
Printing	n/a	
Color	n/a	
Frequency	n/a	

**Packaging**


Box	308mmx290mmx85 mm	Box A / Printed CQR
-----	-------------------	---------------------

**Labelling**

Barcode	5060399120036 Yellow
Artwork No:	6404

**Gross Weight (nominal)**

1.945Kgs
----------

 <p><i>Not to scale</i></p>	<p>Issue 02 Date 03/07/2014 CRJ</p>	<p>CQR Security Tarran Way Ind Est Moreton Wirral CH46 4TH www.cqr.co.uk</p>
--	---	--

Group	Signal Cores	Power Cores
Max conductor DC Nominal resistance	94.6 Ω/Km	n/a
Rated Voltage	50V	n/a
Insulation resistance @20°C	≈ 200 MΩ/Km	n/a

Thermal Characteristics	
Rated Temperature	-10°C to +70°C

Colour Table		
Signal	Power	Status
	Red	✗
	Black	✗
White		✓
Red		✓
Yellow		✓
Green		✓
Grey		✗
Orange		✗
Turquoise		✗
Brown		✗
Violet		✗
Black		✗
Blue		✗
Pink		✗
White / brown stripe		✗
White / violet stripe		✗
White / green stripe		✗
White / blue stripe		✗
White / grey stripe		✗
White / yellow stripe		✗
White / black stripe		✗
White / red stripe		✗

Customer
ADI Benelux

Standards
N/A