

DC102

Surface mount contact, screw terminals

Easy Installation

The DC102-series are ideal for residential and commercial applications where terminal connections are preferred. The unit features positive clamping terminals with anti-rotation lugs and captured screws with combination heads. These features allow for easy, quick installations.

Comprehensive Range

The range includes wide gap, SPDT and biased versions for higher security. This makes it one of the most popular contacts available in the industry today.

Durability and dependability

These high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory.

High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



Standard Features

- Ideal for residential and commercial
- Convenient surface mounting
- Versions with built-in resistors available

DC102

Surface mount contact, screw terminals

Specifications

Operating gap	18 mm (max.)
Connections	Screw
Contact type	NC
Dimensions (W x H x D)	63 x 12 x 19 mm
Colour	White

Ordering Information

Part No.	Description
DC102	Surface mount contact, screw terminals
DC102B	Surface mount contact with screw terminals - brown
DC102R4.7	Surface mount contact with screw terminals - 4.7K
DC102BR4.7	Surface mount contact - screw terminals - brown - 4.7K
DC137	Surface mount contact, screw terminals - wide gap 37 mm
DC123	Surface mount contact, screw terminals
DC104	Surface mount contact, screw terminals - biased
DC1906T	Spacer for DC102, DC123, DC137, DC104
DC1906TM	

