

## HARPER 100

Cod. HP100SE080340



### Introduction

HARPER100 series self-contained LED emergency light with self-extinguishing RAL9003 white polycarbonate body and PMMA reflector with no photobiological risk (RG0). Wall, ceiling and flush mount installation. Power supply 220/230 Vac, 50-60 Hz. Type Non-Maintained or Public Show; luminous flux in emergency 130 lm. Rechargeable LiFePO<sub>4</sub> battery @ 1.5 Ah included; charging time 12 h; minimum autonomy 2 h. Protection rating IP40, double insulated, operating temperature 0 °C ÷ 50 °C. Dimensions: 122 x 255 x 38 mm.


### Description

Product series	HARPER 100
Product type	Emergency luminaire
Version	Standard
Type	Non-Maintained, Public Show
Dimensions	Height 122 mm, Length 255 mm, Depth 38 mm

### Technical specifications

Installation	Wall, ceiling, surface/false ceiling mount
Power supply	220/230 Vac, 50-60 Hz
Absorbed power in W	1 W
Current absorbed from Mains	120 mA
Battery	N.1 LiFePO <sub>4</sub> 3.2 V 1.5 Ah
Autonomy	2 h
Total charging time	12 h
Body	White Polycarbonate RAL9003
Glow wire	850 °C
Diffuser	PMMA laser finish
IP Protection rating	IP40
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 50°C
Additional information	Test button
Compliant to standards	EN 60598-1, EN 60598-2-22, EN 61547, EN 55015 EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-7
Photobiological risk	RG0 (exempt) according to EN 62471

Light source	LED
Colour temperature	6000K
Min. luminous flux in emergency	130 lm
Lum. flux in Maintained mode	-



**INIM ELECTRONICS s.r.l.**

Via dei Lavoratori, 10 Loc. Centobuchi 63076 Montepandone (AP) ITALY  
Tel. +39 0735 705007 Fax +39 0735 704912 [info@inim.biz](mailto:info@inim.biz) [www.inim.biz](http://www.inim.biz)

**inim**  
ELECTRONICS