

AS630

Outdoor siren with single amber beacon - inox cover



Standard Features

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Automatic polarity selection
- Independent hold-off for both : beacon & siren
- Choice of cut-off time

AS630

Outdoor siren with single amber beacon - inox cover

Specifications

Power supply	13.0 to 14.2 VDC
Standby current	25 mA
Current consumption	600 mA
Sound output at 1 m	120 dB
Frequency	1.8 to 2.8 kHz
Cut-off timer	Preset at 3 min. Adjustable 5 min., 10 min., 20 min.
Operating temperature	-25 to +55°C
Self-activating (with battery)	Yes
Recommended battery	1.2/7.2 Ah
Material	Inox
Weight	3 kg
Dimensions (W x H x D)	210 x 300 x 87 mm
Beacon for all types	
Supply voltage	13.0 to 14.2 VDC
Operating current	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute
Spike suppression network	Standard fitted

Ordering Information

Part No.	Description
AS630	Outdoor siren with single amber beacon - inox cover
BS121N	Sealed Lead-Acid Battery - 12V 1.2Ah
BS127N	Sealed Lead-Acid Battery - 12V 7.2Ah
AS600FLASH	Flash module for AS 600 Series