

# KEYPADS & CARD READERS



## Galeo/W | 26-Bit Wiegand Back-Lit Keypad



- Heavy-duty ZAMAK cast alloy (Zinc, Aluminium, Magnesium and Copper)
- Eye-catching bright blue back-lighting
- Potted electronics
- Integrated Piezo/Buzzer
- Power requirements: 12Vdc

## KCP/BP/26W | 26-Bit Wiegand Keypad



- Stainless Steel construction
- 26-Bit Wiegand output
- Call button
- Potted Electronics
- Integrated Piezo/Buzzer
- Power requirements: 12Vdc

## DGLP WLC DGLP FN WLC | Wiegand Proximity Reader

### DGLP FN WLC



- Rugged polycarbonate
- Selectable CDV® Wiegand output, 26, 30 or 44 bit format
- Compatible with CDV, Centaur (Position Technology) and other 26-bit format.
- Up to 15cm (6 in) read range
- Red/Green LEDs and Buzzer
- Power requirements: 12Vdc

### DGLP WLC

## DGLI WLC DGLI F WLC | Wiegand Proximity Reader

### DGLI F WLC



- Stainless steel proximity reader
- Dust/Weather/Vandal resistant
- Selectable CDV® Wiegand output, 26, 30 or 44 bit format
- Compatible with CDV, Centaur (Position Technology) and other 26-bit format.
- Up to 10cm (4 in) read range
- Red/Green LEDs and Buzzer
- Power requirements: 12Vdc

### DGLI WLC

## DGLP/60/W | Wiegand Long Range Reader



- 60 cm (23.5 in) read range
- Selectable CDV® Wiegand output: 26, 30 or 44 bit format
- Compatible with CDV, Centaur (Position Technology) and other 26-bit format.
- Red/Green LEDs and Buzzer
- Operating temp.: -30°C to 60°C
- Power requirements: 12Vdc

## PROMI ECO | 1-Door Stand-Alone Keypad



- Controller built-in
- 100 codes (3 to 8 digits)
- Request-to-exit input
- Easy to configure
- Audible and visual feedback
- Power requirements: 12Vdc/ac

## KCP/BP | Remote Keypad



- Remote keypad for PROMI or DG1
- High security stainless steel construction
- Call button
- Audible feedback buttons
- Programming made from the "host" keypad.
- Power requirements: 12Vac/dc

## DGLIE | Flush Mount Proximity Reader



- Stainless steel flush mount proximity reader
- Remote reader for PROMI500, DGPROX and PROMI1000
- Dust/Weather/Vandal resistant
- 10cm (4 in) read range
- Operating temp.: -30°C to 60°C
- Power requirements: 12Vdc

## Galeo | Back-Lit Keypad with Remote Controller



- 100 User Codes of 4 to 5 digits
- Request-to-exit input
- Audible feedback buttons
- Power: 12/48Vdc or 12/24Vac
- GALEO: 1 relay output  
GALEO2: 2 relay outputs  
GALEO3: 3 relay outputs
- Timed ( 1 to 99 sec.) or latched output

## CBB | Keypad with Controller Built-in



- Stainless steel keypad
- 100 user codes (4 or 5 digits)
- 2 form C relay outputs and 1 N.O. output, timed ( 1 to 99 sec.) or latched
- 12-digit metallic braille keys
- Audible and visual feedback
- Potted electronics
- Power requirements: 12/24Vac/dc

## KCI | Keypad with Remote Controller



- Stainless steel keypad
- 100 user codes (4 or 5 chiffres)
- Request-to-exit input
- Audible feedback buttons
- Power requirements: 12/24Vac/dc
- KCI: 1 relay output  
KCI2: 2 relay outputs  
KCI3: 3 relay outputs
- Timed ( 1 to 99 sec.) or latched output

## KCIE/S/BP | Keypad with Controller Built-in



- Stainless steel keypad
- 100 user codes (4 or 5 digits)
- 1 form C relay output (8A/250V), timed ( 1 to 99 sec.) or latched
- Audible feedback buttons
- Potted electronics
- Power requirements: 12/24Vac/dc
- Available with call button for request-to-enter: KCIE

## KCIL | Illuminated Keypad with Remote Controller



- Illuminated stainless steel keypad
- 100 user codes (4 or 5 digits)
- Audible feedback buttons
- Request-to-exit input
- Push button for request-to-enter
- Power requirements: 12/24Vac/dc
- KCIL: 1 relay output  
KCIL2: 2 relay outputs  
KCIL3: 3 relay outputs
- Timed ( 1 to 99 sec.) or latched output

## KCIEN/SBP | Illuminated Keypad with Controller Built-in



- Illuminated stainless steel keypad
- 100 user codes (4 to 6 digits)
- 2 form C outputs (8A/250V), timed (1 to 99 sec.) or latched
- Audible feedback buttons
- Request-to-exit input
- Potted electronics
- Power requirements: 12/24 Vac or 12/48 Vdc
- Available with call button for request-to-enter: KCIEN

## KCIN | Illuminated Keypad with Remote Controller



- Illuminated stainless steel keypad
- 100 user codes (4 or 5 digits)
- Audible feedback buttons
- Request-to-exit input
- Power: 12/24 Vac or 12/48 Vdc
- KCIN: 1 relay output  
KCIN2: 2 relay outputs  
KCIN3: 3 relay outputs
- Timed ( 1 to 99 sec.) or latched output

## PROFIL100EC | Keypad with Remote Controller



- Illuminated stainless steel keypad
- 100 user codes (4 or 5 digits)
- 2 form C outputs (8A/250V), timed (1 to 99 sec.) or latched
- Audible and visual feedback
- Request-to-exit input
- Potted electronics
- Power requirements: 12/24 Vac or 12/48 Vdc

# STAND-ALONE SYSTEMS



## PROMI / DG1 | 2-Door Stand-Alone Keypad



PROMI



DG1

- Surface mount keypad
- 500 user codes (5 digits)
- Audible & Visual feedback
- 1 form C output and 1 N/O output, timed (1 to 99 sec.) or latched
- 2 request-to-exit inputs
- All programming stored in non-volatile EEPROM memory
- Power requirements: 12Vac/dc
- Consumption: 120mA
- Optional: remote keypad KCP/BP (see page 9)

## PROMI500 / DGPROX | 1-Door Stand-Alone Proximity Reader and Keypad



PROMI500



DGPROX



- 500 users (proximity badges and/or codes)
- 3 operating modes:
  - Mode 0: badge and code
  - Mode 1: badge only
  - Mode 2: badge or code
- Audible & Visual feedback
- 1 request-to-exit input
- Tamper switch
- 1 form C, door relay output (3A/125V)
- 1 form C, alarm relay output (3A/125V)
- Power requirements: 12VAC/DC

## PROMI1000 | 1-Door Stand-Alone Proximity Reader and Keypad



- 1000 users (proximity badges and/or codes)
- 3 operating modes:
  - Mode 0: badge and code
  - Mode 1: badge only
  - Mode 2: badge or code
- 1000 event memory
- 16 holiday schedules
- Real-time event printing
- Anti-passback
- 1 request-to-exit input + 1 Tamper switch
- Audible & Visual feedback
- 1 form C, door relay output (3A/125V)
- 1 form C, alarm relay output (3A/125V)
- Power requirements: 12Vac/dc

## DGLP / DGLP/FN | Polycarbonate Proximity Reader

### DGLP/FN



DGLP



- Remote readers for PROMI1000, PROMI500 and DGPROX
- Surface mount
- Up to 50M (164ft) between the reader and the controller
- Up to 15cm (6 in) read range
- LED visual feedback
- Power requirements: 12V ac/dc

## DGLI / DGLI/F | Stainless Steel Proximity Reader

### DGLI/F



DGLI



- Remote readers for PROMI1000, PROMI500 and DGPROX
- Vandal resistant
- Up to 50M (164ft) between the reader and the controller
- Up to 10cm (4") read range
- LED visual feedback
- Power requirements: 12V ac/dc