

2X-AFR-FB-S-11

Addressable fire panel repeater with fire brigade controls, small cabinet, dutch belgian

Overview

The new 2X-A series life safety control systems bring the speed and functionality of high-end intelligent processing to small to mid-sized addressable applications. Based on 2X series learned experience and with complete backwards compatibility, the new 2X-A features an attractive contemporary design that fits with any decor. With improved robustness, manufactured in metal, special plastics and easy electronics removal, it allows painting in any colour. The main controls are easily located using an improved and robust jog dial.

With high power loop addressable detection, a full line of easily configured option cards and modules, as well as USB and Ethernet® connectivity, these quick-to-configure systems offer versatility that benefits building owners and life safety system installers alike.

The Panel

The fire panel repeaters, with user interface with fire brigade and fire protection controls, supplied in local language come with a 2010-2-NB network board already fitted. Except for having no addressable loops and corresponding programmable outputs, the setup is similar as a normal fire panel. It has its own power supply, 2 conventional relay outputs and 2 supervised outputs, working in pair and dedicated to common fire and fault conditions, as well as 2 user configurable inputs for monitoring and control are available.

Options

The repeaters use a node on the network, similar like a normal panel with a maximum of 32 nodes / 32 loops network of fire panels and fire panel repeaters (including conventional fire panels and fire panel repeaters up to a maximum of 64 conventional zones). Last but not least, in case separate zone indications are required, a 20 or 40 zone fire/fault LED indicator board can be mounted in the panel or repeater with ample space for text.

Network compatible with existing panels, repeaters (existing and new) and conventional panels.

Approvals & compliance

- CE / CPD / EN54-2 / EN54-4 / EN54-21
- WEEE / RoHS compliant



Details

- Local or global repeater with Fire Brigade and Fire Protection controls with or without global control functionality
- Up to 24 LED Zone indicators for Fire and Fault with space for a 4 digit number
- Auto configuration, setup wizards and default regional setup modes
- Ethernet port with TCP/IP for remote diagnostics, maintenance and programming
- EN54 compliant graphical LCD with icons and up to 256 zones
- Improved Jog Dial with 4 soft buttons for simple and intuitive user control
- Aesthetic pleasing design with robust painted steel door
- Easy removable door and chassis for quick and clean installation
- All pluggable connectors
- Up to 72 hours standby time and 30 minutes alarm
- 3 USB ports with memory stick support and RS232 for printer support
- 3 operator level menu structure (20 usernames and passwords)
- Email notification for events directly from the panel (4 user accounts)
- History log memory for 9999 events
- Backwards compatible, supporting site retrofit/upgrades, expansions, replacement
- Comes standard fitted with network board

2X-AFR-FB-S-11

Addressable fire panel repeater with fire brigade controls, small cabinet, dutch belgian

Technische specificaties

Algemeen

Gebruikersinterface	Met brandweerbediening
Netwerkgrootte (nodes)	up to 64

Elektrisch

Type voeding	VAC
Bedrijfsspanning	110 / 240 VAC (+10%/-15%), 50 / 60 Hz ($\pm 5\%$) Mains cable type: 3 x 1.5 mm ² (live, neutral, earth)
Stroomverbruik	Nom. 0.6 / 1.3 A, Max. 1.5 A / 3.15 A Fuse rating: 2 / 4 A

Standby accu

Capaciteit	Max. 2 x 12 V / 18 Ah (use supplied cables)
Opladen	27.3 V at 20°C ; 36 mV/°C
Lage accuspanning waarschuwingsdrempel	23.6 VDC $\pm 1\%$ at 25°C
Batterijen ondersteund in behuizing	Max. 2 x 12 V / 18 Ah (use supplied cables)

Fysiek

Vormfactor	Groot
Fysieke afmetingen	446 x 536 x 164 mm (W x H x D)
Netto gewicht	7.4 kg (without battery)
Verzendgewicht	10.1 kg
Kleur	Wit (RAL 9003)
Type montage	Oppervlaktemontage
Kabelinvoeren	18 (20 mm) / 2 (20 mm) / 2 removable plates (top / bottom / back)
Materiaal	Staal (geverfd)

Omgeving

Bedrijfstemperatuur	-5 to +40°C
Opslagtemperatuur	-20 to +50°C
Relatieve vochtigheid	10 to 95% noncondensing
Omgeving	Indoor
IP-classificatie	IP30, indoor use only

Regelgevend

Conformiteit	CPD, RoHS, WEEE
Certificering	EN54-13, EN54-2, EN54-21, EN54-4



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 19 October 2023 - 12:45