

2X-AF1-FB-S



2X-AF1-FB-S

Technical specifications

General

| | |
|--|----------------------------|
| User interface | With fire brigade controls |
| Maximum system capacity (device count) | up to 32512 |
| Network size (nodes) | up to 16 |

Electrical

| | |
|-------------------|-----|
| Power supply type | VAC |
|-------------------|-----|

Loop

| | |
|-----------------------|---|
| Maximum loop capacity | 1 |
|-----------------------|---|

Zone

| | |
|-----------------------|-----------|
| Maximum zone capacity | up to 512 |
|-----------------------|-----------|

Input

| | |
|----------------|---|
| Input quantity | 2 |
|----------------|---|

Physical

| | |
|---------------|------------------|
| Form factor | Small |
| Colour | White (RAL 9003) |
| Mounting type | Surface mount |
| Material | Steel (painted) |

Environmental

| | |
|-------------|--------|
| Environment | Indoor |
|-------------|--------|

Regulatory

| | |
|---------------|----------------------------------|
| Compliance | CPD, RoHS, WEEE |
| Certification | EN54-13, EN54-2, EN54-21, EN54-4 |



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 15 March 2024 - 12:59