

DMN700Y03-KITR

Conventional MCP, Surface Mount, RED, 100Ω & Free Contact, Resettable

General

DMN700Y03-KITR is a yellow manual call point for surface mount applications. It offers a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a resettable break glass and test key.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



Details

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options available
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

DMN700Y03-KITR

Conventional MCP, Surface Mount, RED, 100Ω & Free Contact, Resettable

Technical specifications

Isolation

Series resistance	NA
-------------------	----

Physical

Physical dimensions	92 x 115 x 59 mm (W x H x D)
---------------------	------------------------------

Net weight	110 g
------------	-------

Colour	Yellow
--------	--------

Material (body)	PC/ABS
-----------------	--------

Environmental

Operating temperature	-10 to +55°C
-----------------------	--------------

Storage temperature	-10 to +55°C
---------------------	--------------

Relative humidity	0 to 95% noncondensing
-------------------	------------------------

Environment	Indoor
-------------	--------

IP rating	IP24D
-----------	-------

Cable Termination

	0.5 to 2.5 mm ²
--	----------------------------

Max. contact rating (resistive load)

	2A @ 30 VDC
--	-------------



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 23 July 2021 - 9:47