

## SC-33-0120-0001-99 SmartCell Red Sounder and Ceiling-Beacon (VAD White Flash)

#### **Overview**

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



#### **Details**

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

# SC-33-0120-0001-99

SmartCell Red Sounder and Ceiling-Beacon (VAD White Flash)

### **Technical specifications**

Wireless frequency	868 MHz
Sounder	
Output level	92 dB(A) at 1 m max.
Selectable tones	32
Output level adjustment	High or low
VAD	
Colour	white flash
Rating	C-3-12
Flash frequency	0.5 Hz (1 flash, every 2 seconds)
Physical	
Physical dimensions	110 x 79 mm (Ø x D)
Net weight	0.2 kg
Colour	Red
Mounting type	Ceiling mount
Mounting position	Ceiling
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries)
	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C
Standards & regula	tion
Compliancy	CE
Certification	CPR
Standards	EN54-3
	EN54-13
	EN54-23

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

