

# SC-31-0200-0001-99 SmartCell White Sounder

#### **Overview**

The SmartCell Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



#### **Details**

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

## SC-31-0200-0001-99 SmartCell White Sounder

### **Technical specifications**

Wireless frequency	868 MHz
Sounder	
Output level	95 dB(A) at 1 m max.
Selectable tones	32
Output level adjustment	High or low
Physical	
Physical dimensions	110 x 72 mm (Ø x D)
Net weight	0.2 kg
Colour	White
Mounting type	Wall mount
Mounting position	Wall
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride
	batteries (Fanso or Titus)
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries)
	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C
Standards & regula	tion
Compliancy	CE
Certification	CPR
Standards	EN54-3
	EN54-13
	EN54-25

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

